

# MVE CryoShipper QWick™ Series



MVE CryoShipper QWick Series utilizes an absorbent wicking material that charges with liquid nitrogen in fewer than two hours, providing the capacity for same-day vapor shipping. Manufactured from durable, lightweight aluminum, they employ a hydrophobic compound which absorbs the liquid nitrogen to ensure dry, spill-free shipping.

Protective shipping cartons are available. These containers may be used to ship your samples with a “non-hazardous” classification throughout the world, thus reducing shipping costs and helping to assure sample viability. Equipped with the same capacity and dimensions as the comparable MVE Vapor Shipper Series.

## Features Include:

- **CHARGES IN LESS THAN TWO HOURS**
- Protective shipping carton to ensure upright shipping
- Low liquid nitrogen consumption
- Convenient lightweight packages

## Accessories:




CryoGloves



Vapor Inserts



CryoBlocks



Square Racks



Datalogger



Plastic Boxes



Comparable To	CryoShipper QWick 6/9 SC2/1V	CryoShipper QWick 10/100 SC 4/2V	CryoShipper QWick 14/48 SC 4/3V	CryoShipper QWick 62/180 SC 20/12V	CryoShipper QWick 14/24 MiniMoover	CryoShipper QWick 9/500 Cryoshipper	CryoShipper QWick 10/950 CryoShipper XC
<b>Maximum Storage Capacity</b>							
No. of Canisters	1	1	1	6	1	1 Rack	-
No. of 1/2 cc Straws 10/cane	-	280	120	540	60	-	-
No. of 1/2 cc Straws 1 Level Bulk	88	440	210	780	88	-	-
No. of 1/4 cc Straws 1 Level Bulk	182	938	452	1630	8904	-	-
No. of 1.2 & 2.0 ml Vials 5/cane	-	95	40	150	20	-	-
No. of 1.2 & 2.0 ml Vials 6/cane	9***	106	48	180	24	500	966 (Bulk)
No. of blood bags stored 4R9953	-	-	-	-	-	10	10
<b>Performance</b>							
LN2 Capacity L	1.5	3.6	4.3	12.3	2.9	8.5	10
Static Evaporation Rate* L/day	0.16	0.26	0.20	0.09	0.16	0.80	0.70
Static holding time Days	6	10	14	62	14	9	10
<b>Unit Dimensions</b>							
Neck Opening in. (mm)	1.40 (35)	2.75 (70)	2.00 (51)	2.00 (51)	1.40 (35)	8.50 (216)	8.50 (216)
Overall Height in. (mm)	13.5 (343)	18.4 (468)	19.4 (492)	25.7 (652)	19.5 (495)	21.5 (546)	23.0 (584)
Outer Diameter in. (mm)	7.2 (184)	8.7 (222)	8.7 (222)	14.5 (368)	7.2 (184)	14.5 (369)	15.0 (381)
Canister Height in. (mm)	5 (127)	11 (278)	11 (278)	11 (278)	11 (278)	-	12.5 (317.5‡)
Canister Diameter in. (mm)	1.2 (31)	2.6 (67)	1.8 (46)	1.5 (38)	1.2 (31)	-	-
Weight Empty lb. (kg)	6.0 (2.7)	11.0 (5)	11.5 (5.2)	25.0 (11.4)	9.0 (4)	25.5 (11.6)	30.0 (13.6)
Weight Charged lb. (kg)	8.0 (3.6)	15.0 (6.8)	16.5 (7.5)	42.0 (19)	13.0 (5.9)	39.0 (17.7)	48.0 (21.8)

\* Static evaporation rate and static holding time are nominal. Actual rate and holding time will be affected by the nature of container use, atmospheric conditions, and manufacturing tolerances.

\*\* With center absorbent canister (3 week holding time)

\*\*\* Stored on three half canes

‡ Useable Height

### THREE Year Vacuum Warranty

#### Chart BioMedical

2200 Airport Industrial Dr., Ste. 500  
Ball Ground, GA 30107  
Ph 770-721-7759 • Toll Free 1-800-482-2473  
Fax 770-721-7758  
customerservice.usa@chartindustries.com



#### Chart BioMedical Ltd.

Ph +44(0) 1344 403100 • Fax +44(0) 1344 429224  
customerservice.europe@chartindustries.com

#### Chart Japan Co., Ltd.

Ph + (03) 5776 2670 • Fax + (03) 5776 2676  
customerservice.japan@chartindustries.com

#### Chart Australia Pty Ltd.

Ph + 61 2 974 94 333 • Fax +61 2 974 94 666  
customerservice.australia@chartindustries.com

Copyright © 2010 Chart Industries Ref ML130003 Rev A